



# Shenzhen Keygma Electrical Manufacturing Co., Ltd

**Add:** 3/F,1st Building, No.57 Baozi North Rd, Kengzi Street, Pingshan District, Shenzhen 518122, China  
**ATTN:** Joyce Xia **Skype/Email:** sales@keygma.com **Cel:** 86 17782390947 **Tel:** 86 755 28313373

※ 2016 Version ETL: 5001170



※ Aging Time: 4 Hours on loading


※ 100% One By One Test


※ Capacity: 50K Per Month











## CATALOGUE from KEYGMA

Item No.	Photo	Specification	Features	Packaging type	Packaging contains	QTY	Delivery Time
<b>15A GFCI Outlet</b>							
KG-15		15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE (220V GFCI optional)	<ul style="list-style-type: none"> <li>▪ Meet UL/CUL943,UL498 (cETLus approved)</li> <li>▪ Prevents line-load reversal miswire</li> <li>▪ Automatic end of life detection</li> <li>▪ Auto-monitoring (self-testing)</li> <li>▪ Reset Lockout mechanism</li> <li>▪ Surge Protection (Required by UL943 and CSA)</li> <li>▪ Takes up to 20% less space vs. other GFCIs</li> <li>▪ Operating Temperature from -35°C to 66°C</li> </ul>	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm	1* KG-15 1* Wall plate 1* User Manual 1* Labels 2* Screws	2K	4 weeks
KG-15T		15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE (220V GFCI optional)	<ul style="list-style-type: none"> <li>▪ Meet UL/CUL943,UL498 (cETLus approved)</li> <li>▪ Prevents line-load reversal miswire</li> <li>▪ Automatic end of life detection</li> <li>▪ Auto-monitoring (self-testing)</li> <li>▪ Reset Lockout mechanism</li> <li>▪ Surge Protection (Required by UL943 and CSA)</li> <li>▪ Takes up to 20% less space vs. other GFCIs</li> <li>▪ Operating Temperature from -35°C to 66°C</li> <li>▪ Tamper-Resistant Shutters</li> </ul>	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm	1* KG-15T 1* Wall plate 1* User Manual 1* Labels 2* Screws	2K	4 weeks

KG-15WT		<p>15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE <b>(220V GFCI optional)</b></p>	<ul style="list-style-type: none"> <li>▪ Meet UL/CUL943,UL498 (cETLus approved)</li> <li>▪ Prevents line-load reversal miswire</li> <li>▪ Automatic end of life detection</li> <li>▪ Auto-monitoring (self-testing)</li> <li>▪ Reset Lockout mechanism</li> <li>▪ Surge Protection (Required by UL943 and CSA)</li> <li>▪ Takes up to 20% less space vs. other GFCIs</li> <li>▪ Operating Temperature from -35°C to 66°C</li> <li>▪ Tamper-Resistant Shutters</li> <li>▪ Weather-Resistant (Designed for wet and damp locations to meet the requirements of NEC Section 406.8)</li> </ul>	<p>50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm</p>	<p>1* KG-15WT 1* Wall plate 1* User Manual 1* Labels 2* Screws</p>	2K	4 weeks
<b>20A GFCI Outlet</b>							
KG-20		<p>20 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE <b>(220V GFCI optional)</b></p>	<ul style="list-style-type: none"> <li>▪ Meet UL/CUL943,UL498 (cETLus approved)</li> <li>▪ Prevents line-load reversal miswire</li> <li>▪ Automatic end of life detection</li> <li>▪ Auto-monitoring (self-testing)</li> <li>▪ Reset Lockout mechanism</li> <li>▪ Surge Protection (Required by UL943 and CSA)</li> <li>▪ Takes up to 20% less space vs. other GFCIs</li> <li>▪ Operating Temperature from -35°C to 66°C</li> </ul>	<p>50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm</p>	<p>1* KG-20 1* Wall plate 1* User Manual 1* Labels 2* Screws</p>	2K	4 weeks
KG-20T		<p>20 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE <b>(220V GFCI optional)</b></p>	<ul style="list-style-type: none"> <li>▪ Meet UL/CUL943,UL498 (cETLus approved)</li> <li>▪ Prevents line-load reversal miswire</li> <li>▪ Automatic end of life detection</li> <li>▪ Auto-monitoring (self-testing)</li> <li>▪ Reset Lockout mechanism</li> <li>▪ Surge Protection (Required by UL943 and CSA)</li> <li>▪ Takes up to 20% less space vs. other GFCIs</li> <li>▪ Operating Temperature from -35°C to 66°C</li> <li>▪ Tamper-Resistant Shutters</li> </ul>	<p>50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm</p>	<p>1* KG-20T 1* Wall plate 1* User Manual 1* Labels 2* Screws</p>	2K	4 weeks
KG-20WT		<p>20 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE <b>(220V GFCI optional)</b></p>	<ul style="list-style-type: none"> <li>▪ Meet UL/CUL943,UL498 (cETLus approved)</li> <li>▪ Prevents line-load reversal miswire</li> <li>▪ Automatic end of life detection</li> <li>▪ Auto-monitoring (self-testing)</li> <li>▪ Reset Lockout mechanism</li> <li>▪ Surge Protection (Required by UL943 and CSA)</li> <li>▪ Takes up to 20% less space vs. other GFCIs</li> <li>▪ Operating Temperature from -35°C to 66°C</li> <li>▪ Tamper-Resistant Shutters</li> <li>▪ Weather-Resistant (Designed for wet and damp locations to meet the requirements of NEC Section 406.8)</li> </ul>	<p>50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm</p>	<p>1* KG-20WT 1* Wall plate 1* User Manual 1* Labels 2* Screws</p>	2K	4 weeks

USB Wall Outlet							
KU-15T		15 Amp, 100- 250 Volt, Keygma® Duplex USB Receptacle, Commercial Grade -WHITE (5V 2.1A, 5V 3.1A optional )	<ul style="list-style-type: none"> <li>▪ Meet UL/cUL498 (cETLus approved)</li> <li>▪ FCC passed</li> <li>▪ Max Output: 5V 4.2A for USB ports fast charging</li> <li>▪ Tamper-Resistant Shutters</li> <li>▪ Side Wired &amp; Back Wired</li> <li>▪ LED indicator, Indicating that the USB charging status</li> <li>▪ Short Circuit and Over Current protection.</li> </ul>	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 42*27*31cm	1* KU-15T 1* Wall plate 1* User Manual 2* Screws	2K	4 weeks
KU-15TQ		15 Amp, 100-250 Volt, Keygma® QC3.0 Duplex USB Receptacle, Commercial Grade -WHITE	<ul style="list-style-type: none"> <li>▪ Meet UL/cUL498 (cETLus approved)</li> <li>▪ FCC passed</li> <li>▪ 5V/9V/12V for USB ports fast charging</li> <li>▪ Tamper-Resistant Shutters</li> <li>▪ Side Wired &amp; Back Wired</li> <li>▪ LED indicator, Indicating that the USB charging status</li> <li>▪ Short Circuit and Over Current protection.</li> </ul>	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 42*27*31cm	1* KU-15TQ 1* Wall plate 1* User Manual 2* Screws	2K	4 weeks
Smart Socket							
KU-15TW		WiFi USB Wall Socket 15A 100-250V AC 60Hz USB Ouput:5V 2.4A	<ul style="list-style-type: none"> <li>▪ Support WiFi network,Tuya App</li> <li>▪ Support Amazon Alexa &amp; Google home.</li> <li>▪ Support Smart configure net technology, easy to access settings.</li> <li>▪ Support status tracking, home appliances status timely feedback to your device.</li> <li>▪ Support Max 8 timing task.</li> <li>▪ Support Max 150 WiFi wall socket from one smart phone.</li> <li>▪ Easy installation, easy handling and can be activated immediately and stably.</li> </ul>	50pcs/CTN N.W: 11.5kgs G.W: 12.5kgs Meas: 42*27*31cm	1* KU-15TW 1* User manual	2k	4 weeks
American Standard Recetacle							
KGM-15T		15 Amp, 125 Volt, Keygma® Duplex Receptacle, Commercial Grade -WHITE	<ul style="list-style-type: none"> <li>▪ Meet UL/cUL498 (cETLus approved)</li> <li>▪ FCC passed</li> <li>▪ Side Wired &amp; Back Wired</li> <li>▪ Tamper-Resistant Shutters</li> </ul>	150pcs/CTN N.W: 11.0kgs G.W: 12.0kgs Meas: 53*28*37cm	1* KGM-15 1* Wall plate 1* User Manual 2* Screws	2K	4 weeks

KGM-20T		20 Amp, 125 Volt, Keygma® Duplex Receptacle, Commercial Grade -WHITE	<ul style="list-style-type: none"> <li>▪ Meet UL/cUL498 (cETLus approved)</li> <li>▪ FCC passed</li> <li>Side Wired &amp; Back Wired</li> <li>▪ Tamper-Resistant Shutters</li> </ul>	<ul style="list-style-type: none"> <li>▪ 150pcs/CTN</li> <li>▪ N.W: 11.0kgs</li> <li>▪ G.W: 12.0kgs</li> <li>Meas: 53*28*37cm</li> </ul>	<ul style="list-style-type: none"> <li>1* KGM-20</li> <li>1* Wall plate</li> <li>1* User Manual</li> <li>2* Screws</li> </ul>	2K	4 weeks
KGM-20TA		20 Amp, 125 Volt, Keygma® Duplex Receptacle, Commercial Grade -WHITE	<ul style="list-style-type: none"> <li>▪ Meet UL/cUL498 (cETLus approved)</li> <li>▪ FCC passed</li> <li>Side Wired &amp; Back Wired</li> <li>▪ Tamper-Resistant Shutters</li> </ul>	<ul style="list-style-type: none"> <li>▪ 150pcs/CTN</li> <li>▪ N.W: 11.0kgs</li> <li>▪ G.W: 12.0kgs</li> <li>Meas: 53*28*37cm</li> </ul>	<ul style="list-style-type: none"> <li>1* KGM-20</li> <li>1* Wall plate</li> <li>1* User Manual</li> <li>2* Screws</li> </ul>	2k	4 weeks
<b>Switch</b>							
 KGM-1	Single pole toggle sitch ,15A 125V	<ul style="list-style-type: none"> <li>▪ Single pole toggle sitch</li> <li>▪ 15A,120V</li> <li>▪ Back &amp; Side Wire</li> <li>▪UL &amp; CUL Listed</li> </ul>	<ul style="list-style-type: none"> <li>▪ 500pcs/CTN</li> <li>▪ N.W: 9.5kgs</li> <li>▪ G.W: 10.0kgs</li> <li>Meas: 38x24x40cm</li> </ul>	<ul style="list-style-type: none"> <li>1* KGM-1</li> <li>1* Wall plate</li> <li>2* Screws</li> </ul>	2K	4 weeks	
 KGM-2	3 way toggle switch,15A 125V	<ul style="list-style-type: none"> <li>▪ 3 way toggle Switch</li> <li>▪ 15A,120V</li> <li>▪ Back &amp; Side Wire</li> <li>▪UL &amp; CUL Listed</li> </ul>	<ul style="list-style-type: none"> <li>▪ 500pcs/CTN</li> <li>▪ N.W: 9.5kgs</li> <li>▪ G.W: 10.0kgs</li> <li>Meas: 38x24x40cm</li> </ul>	<ul style="list-style-type: none"> <li>1* KGM-2</li> <li>1* Wall plate</li> <li>2* Screws</li> </ul>	2K	4 weeks	
 KGM-3	Single pole wall switch,15A 125V	<ul style="list-style-type: none"> <li>▪ Single pole Decorative Switch</li> <li>▪ 15A,120V</li> <li>▪ Back &amp; Side Wire</li> <li>▪UL &amp; CUL Listed</li> </ul>	<ul style="list-style-type: none"> <li>▪ 500pcs/CTN</li> <li>▪ N.W: 9.5kgs</li> <li>▪ G.W: 10.0kgs</li> <li>Meas: 38x24x40cm</li> </ul>	<ul style="list-style-type: none"> <li>1* KGM-4</li> <li>1* Wall plate</li> <li>2* Screws</li> </ul>	2K	4 weeks	

 <p>KGM-4</p>	<p>3 way wall switch,15A 125V</p>	<ul style="list-style-type: none"> <li>▪ 3 Way Decorative Switch</li> <li>▪ 15A,120V</li> <li>▪ Back &amp; Side Wire</li> <li>▪UL &amp; CUL Listed</li> </ul>	<p>500pcs/CTN N.W: 12.0kgs G.W: 13.0kgs Meas: 38x24x40cm</p>	<p>1* KGM-5 1* Wall plate 2* Screws</p>	<p>2K</p>	<p>4 weeks</p>
<b>LED Dimmer</b>						
<p>KGM-1A</p>		<p>Single pole,LED Dimmer 120V, 60Hz, 150W, AC</p>	<ul style="list-style-type: none"> <li>▪ Single pole,LED Dimmer</li> <li>▪ 120V, 60Hz, 150W, AC</li> </ul>	<p>100pcs/CTN N.W: 10.0kgs G.W: 11.0kgs Meas: 37x24x24cm</p>	<p>1* KGM-1A</p>	<p>1k 4 weeks</p>
<p>KGM-11A</p>		<p>3 way LED Dimmer 120V, 60Hz, 150W, AC</p>	<ul style="list-style-type: none"> <li>▪ 3 way LED Dimmer</li> <li>▪ 120V, 60Hz, 150W, AC</li> </ul>	<p>100pcs/CTN N.W: 10.0kgs G.W: 11.0kgs Meas: 37x24x24cm</p>	<p>1* KGM-11A</p>	<p>1k 4 weeks</p>