







E-CATALOG

ATTN: Amos Du


E-mail: sales@keygma.com






Item No.	Photo	Specification	Features	Packaging type	Packaging contains	QTY	Delivery Time
15A GFCI Outlet							
KG-15		15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE	<ul style="list-style-type: none"> ▪ Meet UL/CUL943,UL498 (cETLus approved) ▪ Prevents line-load reversal miswire ▪ Automatic end of life detection ▪ Auto-monitoring (self-testing) ▪ Reset Lockout mechanism ▪ Surge Protection (Required by UL943 and CSA) ▪ Takes up to 20% less space vs. other GFCIs ▪ Operating Temperature from -35°C to 66°C 	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm	1* KG-15 1* Wall plate 1* User Manual 1* Labels 2* Screws	2K	4 weeks
KG-15T		15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE	<ul style="list-style-type: none"> ▪ Meet UL/CUL943,UL498 (cETLus approved) ▪ Prevents line-load reversal miswire ▪ Automatic end of life detection ▪ Auto-monitoring (self-testing) ▪ Reset Lockout mechanism ▪ Surge Protection (Required by UL943 and CSA) ▪ Takes up to 20% less space vs. other GFCIs ▪ Operating Temperature from -35°C to 66°C ▪ Tamper-Resistant Shutters 	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm	1* KG-15T 1* Wall plate 1* User Manual 1* Labels 2* Screws	2K	4 weeks
KG-15WT		15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE	<ul style="list-style-type: none"> ▪ Meet UL/CUL943,UL498 (cETLus approved) ▪ Prevents line-load reversal miswire ▪ Automatic end of life detection ▪ Auto-monitoring (self-testing) ▪ Reset Lockout mechanism ▪ Surge Protection (Required by UL943 and CSA) ▪ Takes up to 20% less space vs. other GFCIs ▪ Operating Temperature from -35°C to 66°C ▪ Tamper-Resistant Shutters ▪ Weather-Resistant (Designed for wet and damp locations to meet the requirements of NEC Section 406.8) 	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm	1* KG-15WT 1* Wall plate 1* User Manual 1* Labels 2* Screws	2K	4 weeks

20A GFCI Outlet



KG-20		20 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE	<ul style="list-style-type: none"> ▪ Meet UL/CUL943,UL498 (cETLus approved) ▪ Prevents line-load reversal miswire ▪ Automatic end of life detection ▪ Auto-monitoring (self-testing) ▪ Reset Lockout mechanism ▪ Surge Protection (Required by UL943 and CSA) ▪ Takes up to 20% less space vs. other GFCIs ▪ Operating Temperature from -35°C to 66°C 	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm	1* KG-20 1* Wall plate 1* User Manual 1* Labels 2* Screws	2K	4 weeks
KG-20T		20 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE	<ul style="list-style-type: none"> ▪ Meet UL/CUL943,UL498 (cETLus approved) ▪ Prevents line-load reversal miswire ▪ Automatic end of life detection ▪ Auto-monitoring (self-testing) ▪ Reset Lockout mechanism ▪ Surge Protection (Required by UL943 and CSA) ▪ Takes up to 20% less space vs. other GFCIs ▪ Operating Temperature from -35°C to 66°C ▪ Tamper-Resistant Shutters 	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm	1* KG-20T 1* Wall plate 1* User Manual 1* Labels 2* Screws	2K	4 weeks
KG-20WT		20 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Keygma® Duplex Receptacle, Commercial Grade, Feed-Thru, Modular Terminals, Steel Strap – WHITE	<ul style="list-style-type: none"> ▪ Meet UL/CUL943,UL498 (cETLus approved) ▪ Prevents line-load reversal miswire ▪ Automatic end of life detection ▪ Auto-monitoring (self-testing) ▪ Reset Lockout mechanism ▪ Surge Protection (Required by UL943 and CSA) ▪ Takes up to 20% less space vs. other GFCIs ▪ Operating Temperature from -35°C to 66°C ▪ Tamper-Resistant Shutters ▪ Weather-Resistant (Designed for wet and damp locations to meet the requirements of NEC Section 406.8) 	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 37*25*22cm	1* KG-20WT 1* Wall plate 1* User Manual 1* Labels 2* Screws	2K	4 weeks

USB Wall Outlet

KU-15T		15 Amp, 125 Volt, Keygma® Duplex USB Receptacle, Commercial Grade -WHITE (5V 2.1A, 5V 3.1A optional)	<ul style="list-style-type: none"> ▪ Meet UL/cUL498 (cETLus approved) ▪ FCC passed ▪ Max Output: 5V 4.2A for USB ports fast charging ▪ Tamper-Resistant Shutters ▪ Side Wired & Back Wired ▪ LED indicator, Indicating that the USB charging status ▪ Short Circuit and Over Current protection. 	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 42*27*31cm	1* KU-15T 1* Wall plate 1* User Manual 2* Screws	2K	4 weeks
--------	---	---	---	---	---	----	---------

KU-15TQ		15 Amp, 100-250 Volt, Keygma® QC3.0 Duplex USB Receptacle, Commercial Grade -WHITE	<ul style="list-style-type: none"> ▪ Meet UL/cUL498 (cETLus approved) ▪ FCC passed ▪ 5V/9V/12V for USB ports fast charging ▪ Tamper-Resistant Shutters ▪ Side Wired & Back Wired ▪ LED indicator, Indicating that the USB charging status ▪ Short Circuit and Over Current protection. 	50pcs/CTN N.W: 10.5kgs G.W: 11.5kgs Meas: 42*27*31cm	1* KU-15TQ 1* Wall plate 1* User Manual 2* Screws	2K	4 weeks
Recetacle							
KGM-15T		15 Amp, 125 Volt, Keygma® Duplex Receptacle, Commercial Grade -WHITE	<ul style="list-style-type: none"> ▪ Meet UL/cUL498 (cETLus approved) ▪ Side Wired & Back Wired ▪ Tamper-Resistant Shutters 	150pcs/CTN N.W: 11.0kgs G.W: 12.0kgs Meas: 53*28*37cm	1* KGM-15 1* Wall plate 1* User Manual 2* Screws	2K	4 weeks
KGM-20T		15 Amp, 125 Volt, Keygma® Duplex Receptacle, Commercial Grade -WHITE	<ul style="list-style-type: none"> ▪ Meet UL/cUL498 (cETLus approved) ▪ Side Wired & Back Wired ▪ Tamper-Resistant Shutters 	150pcs/CTN N.W: 11.0kgs G.W: 12.0kgs Meas: 53*28*37cm	1* KGM-20 1* Wall plate 1* User Manual 2* Screws	2K	4 weeks
Switch							
KGM-4		Single pole wall switch, 15A 125V	<ul style="list-style-type: none"> ▪ Single pole Decorative Switch ▪ 15A, 120V ▪ Back & Side Wire 	500pcs/CTN N.W: 9.5kgs G.W: 10.0kgs Meas: 38x24x40cm	1* KGM-4 1* Wall plate 2* Screws	2K	4 weeks
KGM-5		3 way wall switch, 15A 125V	<ul style="list-style-type: none"> ▪ 3 Way Decorative Switch ▪ 15A, 120V ▪ Back & Side Wire 	500pcs/CTN N.W: 12.0kgs G.W: 13.0kgs Meas: 38x24x40cm	1* KGM-5 1* Wall plate 2* Screws	2K	4 weeks

LED Dimmer

KGM-1A		<p>Single pole,LED Dimmer 120V, 60Hz, 150W, AC</p>	<ul style="list-style-type: none"> ▪ Single pole,LED Dimmer ▪ 120V, 60Hz, 150W, AC 	<p>100pcs/CTN N.W: 10.0kgs G.W: 11.0kgs Meas: 37x24x24cm</p>	<p>1* KGM-1A 1* Wall plate 2* Screws</p>	1k	4 weeks
KGM-11A		<p>3 way LED Dimmer 120V, 60Hz, 150W, AC</p>	<ul style="list-style-type: none"> ▪ 3 way LED Dimmer ▪ 120V, 60Hz, 150W, AC 	<p>100pcs/CTN N.W: 10.0kgs G.W: 11.0kgs Meas: 37x24x24cm</p>	<p>1* KGM-11A 1* Wall plate 2* Screws</p>	1k	4 weeks